# A guide to Arndt & Herman Cellular PVC Mouldings installation, painting and touch-up

### Installation

Here is what you will need for installation:

A miter box for Coping saw cutting accurate 45° Tape measure

and 90° angles Glue Small, fine-tooth saw Pencil Hammer **Putty stick** Nail set C-clamp

Finishing nails

# **Cutting cellular PVC mouldings**

Standard woodworking equipment may be used for cutting Arndt & Herman Cellular PVC Mouldings. Always miter or bevel cut at joints and corners. The use of PVC Cement is recommended for all corners especially on larger moulding patterns (i.e. larger than 2" wide) in addition to cross nailing of the joint. Maximum spacing for nailing should be reduced on both sides of joints and corners.

# Nailing cellular PVC mouldings

Mechanical fasteners may be used on Arndt & Herman Cellular PVC Mouldings keeping in mind the appropriate fastener for the specific product and end use. Nails should be placed 12" on center when possible. Pre-drilling is required for nailing at a temperature of 32° or below, Smaller patterns like Back Bands, Base Caps and Shoe Moulds may be nailed with smaller nails such as 16 ga, or 18 ga, wire brads. Patterns larger than 2" in width should be nailed with 6d or 8d nails either pneumatically or by hand. Typical non-rusting or coated fasteners are highly recommended.

# Touching up cellular PVC mouldings

Four recommended touch-up products are listed below for use with Arndt & Herman Cellular PVC Mouldings, Caution: Solvent-based fillers should not be used. Dap® "All Purpose" Painter's Putty: Minwax® High Performance Wood Filler; Elmer's® Fill-N-Finish Light Wood Filler; Sherwin-Williams Shrink-free Spackling

# **Painting cellular PVC mouldings**

While Arndt & Herman Cellular PVC Mouldings' Readi Finish™ is prefinished and does not require painting, it may be painted a desired color using oil-based or acrylic latex paints. Readi Finish™ is backed with a 10-year finish warranty against discoloration. Using very dark colors is not recommended for painting. Dark-colored paints, such as black, crimson red and hunter green, may fade with time and would require repainting.

# Selecting adhesives for cellular PVC mouldings

The chart below indicates the best adhesives for bonding Arndt & Herman exterior mouldings to wood, steel, drywall and masonry.

Please note that several familiar brands of adhesive were used, but a large number still remain untested. Therefore, individual needs may require a simple check to ensure adequate product performance.

Testing of samples was done under specific laboratory conditions. Individual circumstances may vary.

Adhesive/Sealant	Wood	Steel	Drywall	Masonry
Dow® 100% Silicone	Fair	Fair	Good	
30 Dap® 230 Latex	Fair	Poor	Good	
Tru Test (TruValue®)	Good	Poor	Good	
Contech PL-400	Fair	Fair	Good	
G.E.® Silicone	Fair	Good	Good	
Liquid Nails®	Good	Fair	Good	Good
OSI QuickBond®	Good	Poor	Good	Good
DAP® Better Than Nails	Good	Good	Fair	Good

Arndt & Herman offers a wide selection of no-rot, low-maintenance cellular PVC exterior mouldings. High-quality mouldings that have the look of wood combined with the long-lasting durability of cellular PVC to give homeowners more time to be creative with their lifestyles.

### Wood look with low maintenance

Arndt & Herman exterior mouldings are cellular PVC made from a custom blend of resins specially formulated to ensure that you get the look of wood and, all of our exterior mouldings are moisture proof and insect proof for an enduring exterior.

### Easy installation with cellular PVC mouldings

Arndt & Herman exterior mouldings provide easy installation and trimming of durable, decorative millwork. Because the PVC is cellular, these products cut and nail better than wood and can be installed with either nails or glue. Installation can be done once and done right with every Arndt & Herman exterior moulding product, saving time

### No splitting or cracking

The custom-blended resin extrusions of Arndt & Herman exterior mouldings are designed to minimize expansion and contraction from temperature changes, eliminating the worries of splitting and cracking that occur with wood.

### 10-year factory finish warranty

Prefinished and ready to use, all Arndt & Herman exterior mouldings products also may be repainted to match a home's individual look. Backed by a 10-year Readi™ Finish warranty, these products are quaranteed to experience no UV discoloration.

Arndt & Herman exterior mouldings provide many solutions for a home's exterior such as: exterior trim, door frames, windows, doors. cornice and crowns, garage doors, fascias/frieze boards, decks, column covers, porches, ceilings and wainscoting. Try them and be creative with new uses.





- Highest quality cellular PVC
- Quick and easy installation
- ReadiFinish<sup>™</sup> coating no discoloration
- Prefinished and ready for installation
- Moisture-proof and insect-proof
- Cuts and nails much better than wood

SOLUTIONS

- Will not split, crack or warp
- May be repainted
- 10-year factory finish warranty












# **Moulding Profiles**



A complete set of prefinished, no-rot, low-maintenance, exterior mouldings for home exteriors includes siding accessories, decorative crowns and brick mould. For windows, this will include sills, sill nosing and brick mould.

