



Klumb Forest Products is proud to offer a superior primed FJ Radiata Pine trim board. From excellent quality control and competitive pricing, to reliable deliveries, superior looks and performance – K-Prime insures you will have the highest quality primed trim product available.



Standard Sizes / Profiles:

- 4/4: 23/32"; 16' S4S
- Widths: 2"-12"
- Other Thicknesses, Widths, Lengths and Profiles Available



Product Features:

- 2 Coats Exterior Latex Prime—4 Sides & Ends
- Smoothing Agent Base Coat
- Smooth High Quality Finish
- Exterior and Interior Applications
- 100% Radiata Pine
- 5 Year Limited Warranty
- Handling Instructions on Each Piece



The Klumb Difference:

- Single Source Manufacturing
- On Hand Inventories
- Superior Quality
- Competitive Pricing
- QC Controlled and Verified at Factory

Limited Warranty:

- A. Limited Warranty. In lieu of other expressed or implied warranties of any kind, The Mill warrants to Buyer / Installer on all Products Purchased, for a period of five (5) years from the date of purchase by buyer, that the products shall (i) conform to the products ordered by buyer; (ii) shall be free of defects in material and workmanship that significantly impair the products operation and function; (iii) shall be free from prime coating separation from the lumber core. The Limited Warranty is subject to the conditions that the products are properly stored, transported, and installed in accordance to the following written policy and installed without alteration and in accordance with applicable building codes; and all exposed wood parts are protected with a quality latex paint applied. The Limited Warranty is non-transferable.
- B. Warranty Claims. All Warranty claims must be submitted to Klumb in a timely manner following an initial inspection of delivered products, or upon discovery of latent defects falling within the five year Limited Warranty period. Warranty claims must be in writing and supported by photographs or other evidence of products failure. If evidence concludes the product defect and claim are within Limited Warranty coverage, Hampton shall, in their sole discretion and depending upon the magnitude of the accepted warranty claim, either deliver replacement product or credit the account for the purchase price.
- C. Limitations and Exclusions. Except as may otherwise be provided in a separate written warrant delivered to buyer by Klumb, for specific products sold, the above warranty is the only warranty expressed or implied, Under no circumstances shall Klumb be responsible of incidental or consequential damages, or lost profits, and its liability shall in all instances, be limited to the replacement of the defective product or crediting the account in the amount of the purchase price.

Some states do not allow the exclusion or limitation of incidental or consequential damage, or the length of time an implied warranty lasts. The above stated limitations or exclusions may not apply, depending upon the state in which Buyer maintains its business headquarters.

Proper Storage, Handling and Installations of K-Prime:

- Product must be stored and protected in their packaged form within a roofed complex that provides complete weather protection
- All cuts, nail holes, and dados must be covered with at least 2 coats of exterior latex paint
- Product should always be installed in accordance with the highest industry standards
- Proper application and nailing practices are essential for maximizing the performance and appearance
- Building construction features that maximize performance of exterior wood products include; wide roof overhang, wide flashing at roof edges, correct flashing around doors and windows, effective vapor barriers, end joints are not exposed and at least 18" above ground level
- Hand nailing, with hot-dipped galvanized or stainless fasteners, is recommended so that the factory applied coating system is not broken
- Nail holes should be filled immediately to seal the wood with putty and spot prime before paint
- Remove chalky paint, dirt, etc. and sand to a smooth even finish
- Product must be painted as soon as possible after installation
- Apply two full coats of premium quality exterior house paint as per manufacturers recommendation
- Apply two full coats of premium prime to ends
- Application of the recommended painting specification will provide protection against moisture uptake and therefore minimize dimensional change
- The primer will not protect against moisture uptake when exposed to rain or extreme weather
- Under rain or extreme weather temporary dimensional swelling may occur—it is essential that if swelling is evident, the product must be given time to dry out and return to its equilibrium moisture content and manufactured dimensions before application of any final coating system
- We do not warrant any product which has not been kept dry or which has not been painted according to the above specifications